

# **Technical Data Sheet**

# **Helmold 80 Cutting Rule**

#### **Description**

Helmold® 80 is an extra hard rule recommended for usage in applications that require very high beam strength for straight use only.



## **Physical Properties**

Body Hardness 54 HRC

Bendability Straight work only

Point Thickness 2

Height 0.500" - 0.937"

Bevel Finish Shaved, Buffed, Ground

Bevel Angles 60°

## **Availability & Ordering Information**

Steel rule is available in six bevel profiles:

• CFB (Center Face Bevel)

CFLB (Center Face, Long Bevel)

FB (Flush Bevel)

- MBB (Minimum Back Bevel)
- SFB (Side Face Bevel)
- SFLB (Side Face, Long Bevel)

Helmold 80 is available in three bevel finishes:

- Shaved
- Buffed
- Ground

Steel rule in 30", 36", and meter lengths can be purchased by the piece. Clockwise, anti-clockwise, and dispenser coils are sold in full coils only.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no events shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

