Safety Data Sheet

Classified in accordance 29 CFR 1910.1200

1. Product Identification	
Product Information:	100007592
Product Identifier:	SPRAYWAY 945 SILICONE SPRAY
Recommended Use:	Lubricant
Manufacturer/Importer/Distributor Information:	PLZ Corp. 2651 WARRENVILLE RD, STE 300 DOWNERS GROVE, IL 60515
	800-332-9000
Emergency Telephone:	1-800-424-9300

2. Hazard(s) identification

Classification

Flammable Aerosol, category 1 Aspiration Hazard, category 1 Skin Irritation, category 2 STOT, single exposure, category 3, NE

Label elements

HAZARD PICTOGRAMS



Danger

GHS HAZARD STATEMENTS

- H222 Extremely flammable aerosol.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.

<u><u></u></u>				от л т	EMENTS
ыпэ	PREU	AUTION	IART	SIAI	

Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust, fumes, gas, mist, vapours, or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
0110	

P280	Wear protective gloves
Response P301+P310+P331	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340+P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
Storage	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
Disposal	
P501	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other Information

None

3. Composition/Information on Ingredients

Mixtures

Chemical Identity	CAS Number	Content in Percent (%)*
Propane	74-98-6	25-50
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	25-50
n-Heptane	142-82-5	10-25
Naphtha (Petroleum), Hydrotreated Heavy [<0.1% Benzene]	64742-48-9	2.5-10
Methylcyclohexane	108-87-2	1.0-2.5

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid Measures

SKIN CONTACT: Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Wash skin thoroughly with soap and water for several minutes. If irritation occurs, get medical attention. Remove contaminated clothing. Launder clothing before re-use.

EYE CONTACT: Rinse immediately with plenty of water.

INHALATION: Move to fresh air. Remove victim to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if you feel unwell.

INGESTION: Keep the victim calm and warm. Do NOT induce vomiting. If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

IMPORTANT SYMPTOMS: Inhalation may cause drowsiness or dizziness. Aspiration hazard: Harmful or fatal if swallowed. May cause skin irritation.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Get medical attention if symptoms occur. Immediate medical attention is required for ingestion.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Use fire-extinguishing media appropriate for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Prolonged exposure to temperatures above 50°C / 122°F may cause cans to burst. Vapors may travel considerable distance to a source of ignition and flash back. Combustion may produce carbon dioxide and carbon monoxide.

SPECIAL FIREFIGHTING PROCEDURES: No data available

6. Accidental Release Measures

PERSONAL PRECAUTIONS : Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Leaking cans should be placed in a plastic bag or open pail away from ignition sources until the pressure has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and Storage

HANDLING: Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

SAFE HANDLING ADVICE: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

STORAGE: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

NFPA 30B: Aerosol Level 3

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

······································					
Chemical Name	<u>TLV-TWA</u>	TLV-STEL	PEL-TWA	PEL-CEILING	
Propane	N.E.	N.E.	1000 ppm	N.E.	
Naphtha, (Petroleum), Hydrotreated Light	N.E.	N.E.	100 ppm	N.E.	
n-Heptane	400 ppm	500 ppm	500 ppm	N.E.	
Naphtha (Petroleum), Hydrotreated Heavy [<0.1% Benzene]	N.E.	N.E.	N.E.	N.E.	
Methylcyclohexane	400 ppm	N.E.	500 ppm	N.E.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

ENGINEERING CONTROLS: No data available

Personal Protection

EYE/FACE PROTECTION: Wear goggles/face shield.

SKIN PROTECTION: Wear impervious gloves to prevent skin contact.

RESPIRATORY PROTECTION: Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

HYGIENIC PRACTICES: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and Chemical Properties

Appearance:

••	
Physical State:	Liquid
Form:	Spray Aerosol
Color:	Colorless
Odor:	Solvent
Odor Threshold:	No data available
pH:	No data available
Freeze Point, °C:	No data available
Boiling Point, °C:	7
Flash Point, °C:	Not applicable to aerosols
Flammability (solid, gas):	Flammable Aerosol
Evaporation Rate:	No data available
Combustibility:	Supports Combustion
Explosive Limits, %:	1.0 - 9.5
Vapor Pressure @20°C, PSI:	65-85
Vapor Density:	No data available
Relative Density:	0.630
Solubility in Water:	No data available
Partition Coefficient, n-octanol/water:	No data available
Auto-Ignition Temperature, °C:	No data available
Decomposition temperature, °C:	No data available
Kinematic Viscosity:	No data available

10. Stability and Reactivity

REACTIVITY: Not reactive under normal conditions of use.

STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available

CONDITIONS TO AVOID: Keep away from heat, sparks, flames, and other sources of ignition. Do not puncture or incinerate containers. Dropping containers may cause bursting.

INCOMPATIBILITY: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may produce carbon dioxide and carbon monoxide.

11. Toxicological Information

Information on Likely Routes of Exposure

SKIN CONTACT EFFECTS: May cause irritation, drying, defatting of the skin and dermatitis.

EYE CONTACT EFFECTS: May cause slight irritation with tearing.

INHALATION EFFECTS: May cause central nervous system effects with drowsiness and dizziness.

INGESTION EFFECTS: Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible, or confirmed human carcinogen by IARC, ACGIH, NTP or OSHA.

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

ATE ORAL	5,045 mg/kg
ATE DERMAL	3,764 mg/kg
ATE INHALATION	Not classified for acute toxicity based on available data.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below				
<u>CAS-No.</u>	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l
64742-49-0	Naphtha, (Petroleum), Hydrotreated Light	5,000 mg/kg	3,750 mg/kg	100 mg/l
142-82-5	n-Heptane	5,000 mg/kg	2,000 mg/kg	29.29 mg/l
64742-48-9	Naphtha (Petroleum), Hydrotreated Heavy [<0.1% Benzene]	5,000 mg/kg	6,000 mg/kg	100 mg/l
108-87-2	Methylcyclohexane	>3200 mg/kg Rat	2,000 mg/kg	100 mg/l

N.I. = No Information

Skin Corrosion & Irritation:

Product:		No data available
Components:		
n-Heptane	142-82-5	Causes skin irritation.
Methylcyclohexane	108-87-2	Causes skin irritation.
Serious Eye Damage & Irritation:		
Product:		No data available
Respiratory or Skin Sensitization:		
Product:		No data available
STOT-Single Exposure:		
Product:		No data available
Components:		
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	May cause drowsiness or dizziness.
n-Heptane	142-82-5	May cause drowsiness or dizziness.
Methylcyclohexane	108-87-2	May cause drowsiness or dizziness.
STOT-Repeated Exposure:		
Product:		No data available
Aspiration Hazard:		
Product:		No data available
Components:		
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	May be fatal if swallowed and enters airways.
n-Heptane	142-82-5	May be fatal if swallowed and enters airways.
Methylcyclohexane	108-87-2	May be fatal if swallowed and enters airways.
Naphtha (Petroleum), Hydrotreated Heavy [<0.1% Benzene]	64742-48-9	May be fatal if swallowed and enters airways.
Carcinogenicity:		

Product:

Reproductive Toxicity:	
Product:	No data available
Germ Cell Mutagenicity:	
Product:	No data available
12. Ecological Information	

ECOLOGICAL INFORMATION: No data available

PERSISTENCE: No data available

BIOACCUMULATE: No data available

MOBILITY IN SOIL: No data available

OTHER ECOLOGICAL: No data available

13. Disposal Information

DISPOSAL INFORMATION: Consult with your local, regional and federal agencies for information on proper disposal.

CONTAMINATED PACKAGING : Consult with your local, regional and federal agencies for information on proper disposal.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No data available

DOT	
UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk	N/A
Packing Group:	N/A
ΙΑΤΑ	
UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A
IMDG	
UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A
Marine Pollutant:	Yes

The classification shown In this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory Information

CHEMICAL INVENTORY STATUS:

TSCA On or in compliance with the inventory

DSL

All ingredients in this product are listed on the DSL or are exempt.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:



Warning: This product may contain ingredients known to the state of California to cause Cancer or Reproductive Harm.

Chemical Name	CAS-No.
Toluene	108-88-3
n-Hexane	110-54-3
Ethyl Benzene	100-41-4
Benzene	71-43-2

16. Other Information

Revision Date: 3/20/2024

Datasheet produced by: Regulatory Department

Legend

N/A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

- TLV Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)
- PEL Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended
- TSCA U.S. Toxic Substance Control Act
- DSL Canada Environmental Protection Act: Domestic Substance List

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where the product use and frequency of exposure exceeds that established for the labeled consumer use.

Further Information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the manufacturer's and seller's control. Purchaser and user are responsible for determining the suitability of the product for a particular purpose, adopting precautions for the protection of property and persons, and compliance with all Federal, State, Provincial, and Local laws.

Revision Date: 3/20/2024