



Black Maxx Counterplate

Description

Black Maxx Counterplate offers high mechanical stability, excellent wear resistance, with a thickness tolerance of +/- 0.03mm. Structured surface on one side allows good adhesion without affecting thickness tolerance.

Physical Properties

Color	Black
Density g/cm ³ (ISO1183)	1.50 – 1.77
Flexural Strength, psi (ISO178)	49,312
Tensile strength, psi (ISO527)	26,106
Modular of Elasticity, psi (ISO178)	1,377,858

Ordering Information

SKU	Thickness	SKU	Thickness
080300	0.40 mm	080324	0.80 mm
080303	0.45 mm	080327	0.85 mm
080306	0.50 mm	080330	0.90 mm
080309	0.55 mm	080336	1.00 mm
080312	0.60 mm	080339	1.10 mm
080315	0.65 mm	080341	1.20 mm
080318	0.70 mm	080344	1.30 mm
080321	0.75 mm		

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT